

## OBRF

### "OBRF" 868 MHz RADIO FREQUENCY INTERFACE BOX



868MHz Radio frequency interface box, for wireless communication between PC/master device and weight indicator/repeater. Up to 50 channels, configurable through PC software. Connection through USB or RS232 port (depending on the model).

Working in cooperation with:

**WMS SCALES TECHNOLOGY SRL**  
FAGETU IERII, NR. 54 - 407321 - IARA - ROMANIA  
Tel. 40745312637  
[office@centrul-de-cantare-si-balante.ro](mailto:office@centrul-de-cantare-si-balante.ro)

**The best solution  
for advanced industrial  
applications**

## Technical features OBRFUSB module

- For the connection to PC.
- PVC box.
- Box dimensions (lwxh): 100x60x34mm.
- USB input signal.
- USB/mini USB connecting cable, 1m long.
- Power supply directly from USB port.

## Technical features OBRF232 module

- For the connection to PC.
- IP65 ABS box.
- Box dimensions (lwxh): 120x80x55mm.
- RS232 input signal.
- RS232 connecting cable, 3m long, complete with DB9 pin connector and external power supply.

## Technical features OBRF module

- For the connection to weight indicator/repeater.
- IP65 ABS box.
- Box dimensions (lwxh): 120x80x55mm.
- RS232 input signal.
- RS232 connecting cable, 3m long.
- Power supply from weight indicator/repeater.
- Decoding standard cable colors:

<i><u>Colour</u></i>	<i><u>Meaning</u></i>
YELLOW	TX
PINK	RX
GREY	GND
BROWN	+Vdc (5-12Vdc)

## Operating specification

- Work frequency, from 868 to 870 MHz, which reduces the risk of interferences with the classic radio frequency systems. This work frequency allows also to install new systems in the same environments in which there are weighing systems fitted with the previous interfaces.
- Up to 50 different channels, easily programmable with the programme on PC, in order to install various independent systems in the same work area.
- Max. Functioning distance, in appropriate environmental and installation conditions: up to 70m indoors, and up to 150m outdoors.
- Does not require particular communication protocols, trasmission in transparent manner of any character received in input.

### DETAIL 1



OBRF: 868 MHz radio module with the RS232 port.

### DETAIL 2



OBRF232: 868 MHz radio module with the RS232 port and external power supply.



[www.diniargeo.com](http://www.diniargeo.com)

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena - Italy  
Tel. +39.0536 843418

**WMS SCALES TECHNOLOGY SRL**

FAGETU IERII, NR. 54 - 407321 - IARA - ROMANIA

Tel. 40745312637

[office@centrul-de-cantare-si-balante.ro](mailto:office@centrul-de-cantare-si-balante.ro)

**SALES AND TECHNICAL ASSISTANCE SERVICE**